

**WATER
TENDER**

FIELD OF INTERVENTION **URBAN**



You should appreciate particularly ...

- The standardisation of the components and the modular concept of the bodywork easing the repairs.
- Fulcrum chassis with a belted tank and hydraulic components.
- Bodywork wrap type.
- An optimized volumes of the lockers and their accessibility.
- Corrosion protection offered by :
 - the materials,
 - the process of assembling,
 - the anti-corrosion treatment applied.

Photos and documentation non binding

**CHASSIS CAB
IVECO Eurocargo 150 E 28**

- Power : 205 kW (280 hp)
- Wheel base : 3.690 m
- G.V.W. : 15 tons
- Crew cab, 4 doors, 8 seats.
- Power take-off type ZF NL10 ratio 2.03 – Flange coupling engine ratio wise.

OPTIONAL

- Robotic or automatic gear box.

CAMIVA EQUIPMENT

- Tank : 3,300 L in G.R. polyester.
- Pump : 2,000 l/m 15 bars.
- Bodywork « tubular steel structure », covered with aluminium.
- 1 first aid hose reel.
- 2 mobile reels.
- Sliding steps
- Folding steps (optional)
- Electronic foam mixing system (optional)
- Rear telescopic mast (optional)

E_FT_010_d

Folio 529992