

WATER

TENDER

FIELD OF INTERVENTION

URBAN AREAS



You should appreciate particularly ...

- The standardization of the sub-assemblies derivated from a modular concept and an assembly which facilitate the repairs:
 - Sub-frame with the tank belted on and water pump, all around bodywork on top of it.
- An optimized volume for the lockers and their accessibility.
- The anti-corrosion protection offered by:
 - . The material used,
 - . The assembly process,
 - . The anti-corrosion treatments applied.



Photos and documentation non binding



RENAULT Trucks CHASSIS CAB Type Midlum 270.15

- Power: 194 kW (270 HP)
- Wheelbase: 3,800 m.
- G.V.W.: 15 t.
- Crew Cab , 1+7 places.
- Power Take-Off type 2908, NL/10B 270Nm.

Optional chassis

- Type Midlum 300.15 Power 217 kW (300 HP)
- Automatic or automatised gearbox.

I.M.Camiva EQUIPMENT

- Water Tank : 3300 liters in G.R.P.
 - Pump: 2000 l/mn, 15 bars.
 - Steel treated tubular bodywork structure, panelled with aluminium plates.
 - Sliding low footsteps
 - 1 first aid hose reel.
 - 2 mobile hose reels
- Optional equipment**
- Locker on the top of the equipment.
 - Foldable footsteps.
 - Electronically controlled foam production-

Length = 7,58m ~ width = 2,50m ~ height = 3,20m

E_FT_012_e

Folio 530790