

WATER

TENDER

FIELD OF INTERVENTION

URBAN AREAS



You should appreciate particularly ...

- The standardization of the sub-assemblies derivated from a modular concept and an assembly which facilitate the repairs:
Sub-frame with the tank belted on and water pump, all around bodywork on top of it.
- An optimized volume for the lockers and their accessibility.
- The anti-corrosion protection offered by:
 - . The material used,
 - . The assembly process,
 - . The anti-corrosion treatments applied.



Photos and documentation non binding

RENAULT Trucks CHASSIS CAB

Type: Midlum 270.15

- Power: 194 kW (270 HP)
- Wheelbase: 3,800 m.
- G.V.W.: 15 t.
- Crew Cab, 1+7 places.
- Power Take Off type NL/10 B 270 Nm.

Optional châssis:

- Midlum 300-15 (300 H.P.)
- Automatic/Automatized gearbox

I.M. Camiva EQUIPMENT

- Tank: 3300 liters in G.R.P.
- Pump: 2000 l/m at 15 bars.
- Aluminium bodywork.
- Lower sliding footsteps.
- 1 first aid hose reel.
- 2 mobile hose reels.

Optional equipment

- Locker at the top of the equipment.
- Foldable footsteps.
- Electronic foam production system.

Length = 7,80m ~ width = 2,55m ~ height = 3,20m (ou 3,30m)

E_FT_069_c

Folio 530885