

WATER

TENDER

FIELD OF INTERVENTION

URBAN AREAS



*You should appreciate
particularity ...*

- The standardization of the sub-assemblies derived from a modular concept and an assembly which facilitate the repairs:
 - Sub-frame with the tank belted on and water pump, all around bodywork on top of it.
- An optimized volume for the lockers and their accessibility.
- The anti-corrosion protection offered by:
 - . The material used,
 - . The assembly process,
 - . The anti-corrosion treatments applied.

*Photos and documentation
non binding*

IVECO CHASSIS CAB Eurocargo ML 150 E 28

- Power : 205 kW (280H.P.)
 - Wheelbase: 3,690 m.
 - G.V.W.: 15 t.
 - Crew Cab, 1+7 places.
 - Power Take Off ZF NL 10
- Optional châssis**
- Automatic or automatized gearbox.

I.M.Camiva EQUIPMENT

- Tank: 3300 litres made of G.R.P.
 - Pump: 2000 l/m 15 bars.
 - Aluminium bodywork 6 lockers
 - Lower sliding footsteps.
 - 1 first aid hose reel
 - 2 mobile hose reels.
- Optional equipment**
- Rear mast light.
 - Foldable footsteps.
 - Electronic foam production system.

Length = 7,80m ~ width = 2,55m ~ height = 3,20m (ou 3,30m)