

ROAD RESCUE & WATER TENDER

You should appreciate particularly...

- The standardization of the sub-assemblies derived from a modular concept and an assembly which facilitate the repairs:
 - Sub-frame with the tank belted on and water pump, all around bodywork on top of it.
- An optimized volume for the lockers and their accessibility.
- The anti-corrosion protection offered by:
 - . The material used,
 - . The assembly process,
 - . The anti-corrosion treatments applied.

Photos and documentation non binding

FIELD OF INTERVENTION

URBAN AREAS



RENAULT Trucks CHASSIS CAB Type Midlum 270.15

- Power : 194 kW (270 ch)
- Wheelbase: 4100 m.
- G.V.W.: 15 t.
- Crew Cab, 1+7 places.
- Power Take Off type NL/10B 270 Nm.

Optional châssis

- Midlum 300.15.(300 H.P.)
- Automatic or Automized gearbox.

EQUIPEMENT I.M. Camiva

- Tank: 3300 liters made of G.R.P.
- Pump: 2000 l/m at 15 bars.
- Aluminium bodywork, with aluminium plating.
- Lower sliding footsteps.
- 1 first aid hose reel.
- 2 mobile hose reels.

Optional equipment.

- Locker on the top of the equipment.
- Foldable footsteps.
- Electronic foam production system.



E_FT_071_b

Folio 530894