

**LIGHT
WATER
TENDER**

FIELD OF INTERVENTION

URBAN AREAS



You should appreciate particularly ...

- The standardization of the sub-assemblies derivated from a modular concept and an assembly which facilitate the repairs:
 - Sub-frame with the tank belted on and water pump, all around bodywork on top of it.
- An optimized volume for the lockers and their accessibility.
- The anti-corrosion protection offered by:
 - . The material used,
 - . The assembly process,
 - . The anti-corrosion treatments applied.



Photos and documentation non binding



**RENAULT Trucks CHASSIS CAB
Type : Midlum 220.10/B**

- Power : 161 kW (220 H.P.).
- Wheelbase: 3,20 m.
- G.V.W. : 10 t.
- Crew Cab , 1+6 places.
- Power Take Off on gearbox type NL/10B 270 Nm – ratio 2.03, flange output.
- Non-symmetrical suspensions.

I.M. Camiva EQUIPMENT

- Tank : 2000 liters made of GRP.
- Pump : 1000 l/min at 15 bars.
- Bodywork with protected steel profiles covered with aluminium plates.
- 4 upper lockers closed by shutters.
- 1 first aid hose reel.
- 1 or 2 mobile hose reels.
- Optional equipment**
- Lower lockers with doors.
- Pressure regulation.
- Others on request.

Length = 6,50m ~ width = 2,40m ~ height = 3,20m